


Product datasheet

Specifications

Automatic Transfer Switches

HK-630TN 3P 630A 12kA

Standard	IEC 60947-6-1 / UL1008	
Type	TN type	
Rated operational current, In	630A	
Number of poles	3	
Rated frequency	50/60Hz	
Rated Operational Voltage, Ue	AC600V, DC125V	
Rated Insulation Voltage, Ui	690V	
Impulse Withstand Voltage, Uimp	8kV	
Switch capacity	Class	AC3, DC1
Switching frequency	150 times/h	
Switching sequence	A ↔ B, A ↔ OFF ↔ B	
Operating Time	Break(Opening)	≤ 30ms
	Make Closing	≤ 60ms
	Make delay(Off)	≤ 30ms
Rated short-time withstand current, Icw	12kA	
Rated short-circuit making capacity, Icm	12kA	
Operating Voltage & Current	AC110/120V	24A
	AC220/240V	12A
Control voltage	85 ~ 110% Rated operating voltage	
Withstand Voltage for Main circuit	2500V/60s	
Withstand Voltage for Control circuit	1500V/60s	
Life time	Electric	5000 times
	Mechanic	10000 times
Weight	13kg	
Dimension (W x L x H)	344x145x304mm	



600A ~ 800A	(mm)	
	3P	4P
A	344	405
B	226	287
C	189	250

