

Product datasheet

Specifications

Residual Current Circuit Breaker

MR63E-G4 4P 20A 30mA

| | |
|---|-----------------------------------|
| Standard | IEC/EN 61008-1 |
| Type | MR63EG4 |
| Rated current, I _n | 20A |
| Rated Residual Operating Current (I _{Δc}) | 30 mA |
| Trip Time at I _{Δc} | ≤ 100 ms |
| Number of poles | 3P+N |
| Rated frequency | 50/60Hz |
| Rated Operational Voltage, U _e | 240/415V |
| Rated Insulation Voltage, U _i | 500V |
| Impulse Withstand Voltage, U _{imp} | 4kV |
| Breaking capacity | 6kA, 10kA (Inc) |
| Magnetic Release Setting | + |
| Terminal Capacity (max) | 35 mm ² |
| Protection Class | IP20 |
| Positive Contact Indication | Red-ON, Green-OFF |
| Mounting | Clip on DIN Rail (35 mm x 7.5 mm) |
| Installation Position | Vertical / Horizontal |
| Mechanical Endurance | 20000 times |
| Electrical Endurance | 10000 times |
| Net Weight | 0.102kg |
| Dimensions (H x D x W) | 84.5 x 74.5 x 71 mm |

